



Air operated Valve

Compact size 2-way diaphragm valve
Size : 1/2"

FVAT 2140

Specifications 사양

Orifice size	Ø 10	
Connection size	1/2"	
OP.Temp	5 ~ 80 °C	5 ~ 120 °C 1)
OP.Press(ordinary)	0 ~ 0.5 MPa	0 ~ 0.3 MPa
OP.Press(reverse)	0 ~ 0.3 MPa	0 ~ 0.2 MPa
Air Press	0.4 ~ 0.6 MPa	0.4 ~ 0.6 MPa
Cv	1.304	
Weight	151.5 g	

1) : For hydrofluoric acid or chemicals containing hydrofluoric acid, use the temperature below 80 degrees Celsius.

Applications 사용 분야

- Semiconductor and LCD wet equipment
- Using to control the little flow of coater or developer equipment
- Using to control the little flow of wet spin process equipment
- Chemical supply unit of little capacity
- Microbe, biochemistry and medical fields
- 반도체 및 LCD wet 장비
- Coater, Developer 장비의 소유량 제어용
- Wet spin process 장비의 소유량 제어용
- 소용량 Chemical supply unit
- 미생물 생화학 의학 분야

General 개요

This is compact diaphragm valve as from 1/2" and this durable valve is tested up to 10million cycling times. Since wetted parts are constructed anticorrosive PFA, suitable for DI water or chemical process line.

이 valve는 1/2" Tube size의 중형 Diaphragm valve입니다. 우수한 내구성의 이 Valve는 1000만 Cycle test를 거쳤습니다. 접액부는 우수한 내화학성의 PFA로 만들어져 DI water 및 Chemical 공정에 적합한 제품입니다.

Features 특징

- Wetted parts is made of PFA
- PTFE diaphragm tested to more than a 10million cycles
- 1/2" size connection
- Sleeve insert tube
- NC, NO, Double Acting by air
- Indicator for movement's confirmation, flow control function
- Particle free, none ion contamination
- Ultrasonic washing by DI water & vacuum packing
- PFA 재질로 구성
- 1000만 cycle test를 거친 PTFE diaphragm
- 큰 orifice 구조로 원활한 유체 유동과 적은 압력 손실
- 1/2" size connection
- Sleeve insert tube
- Air 구동의 NC, NO, Double Acting
- 동작 확인용 indicator, 유량 조절 기능 부차
- Particle free, none ion contamination
- Degreasing, DI water로 초음파 세정 및 진공포장

Part name	Material	
	80 °C	120 °C
Body	PFA	
Diaphragm	TFM	TFM
Upper Cover	PP	PPS
Actuator	PP, PPS	PPS
Mounting Plate	PPS, PP	

How to order 주문 방법

FVAT 2140 □ □ - □ □ □ - □ - □ - □ - □
① ② ③ ④ ⑤ ⑥ ⑦ ⑧

① Upper Cover	② Actuator	③ Operating	④ Connection	⑤ Option
S(Standard): PPS(120°C) V : PVDF(Ozone) E: PP(80°C)	S(Standard): PPS(120°C) V : PVDF(Ozone) E: PP(80°C)	C : Normal Close O : Normal Open D : Double Acting	4: 1/2" Z : Z Fitting	0 : No Option 1 : Indicator 2 : Flow Control 3 : By-pass (Body : PTFE) 4 : Flow control + By-pass (Body: PTFE)
				Transistor Cable direction
				3 Sensor NPN Cable length : 2m Operating port side
				4 Sensor PNP Cable length : 2m Opposite side to operating port
				5 Sensor PNP Cable length : 2m Operating port side
				6 Sensor PNP Cable length : 2m Opposite side to operating port
⑥ O - Ring	⑦ Air Port Direction	⑧ Plate Material	Base Plate Type	Diaphragm
V : FKM (VITON) F : ETP K : FFKM	1 2 3 4 	S(Standard): PPS E : PP V : PVDF(Ozone)	B : B Type Plate	T : TFM

Dimension 크기

설계치수는 영업부에 문의 또는 승인도를 요청 바랍니다. 상기 치수는 변경될 수 있습니다.
For exact size of each item, Please contact Sales Dept. Above-mentioned dimensions are changeable.

